

SG7501

Oil Dissipation Factor and Resistivity Meter



SG7501 Oil Dissipation Factor and Resistivity Meter is used to measure dissipation factor, dielectric constant and resistivity for oil. The set is all-in-one structure, with internal oil cup, temperature control, AC bridge, high resistance meter, AC/DC test voltage and standard capacitor etc.

The set is equipped with full digital technique, full automatic measurement, easy to operate and stable in performance. Test results are displayed on a large LCD and output with a micro printer.

Features

Easy to Operate

- ◆ Small cup easy to assemble, use an injector to inject or suck up oil, clean and quick to operate.
- ◆ Only 10ml is needed for one test, excessive oil flow to the waste oil cup.
- ◆ There is no necessity to disassemble cup or stop temperature control while replacing oil.
- ◆ Easy to carry for small and light, suit to on-the-spot test.

High Accuracy

- ◆ 2 channel individual temperature controllers ensure to get even temperature.
- ◆ The unique cup structure enables good repeat stability for cup installation.
- ◆ Advanced precise micro-current bridge makes the set very small in size.
- ◆ High accuracy, being up to the standard of 《GB/T 5654-1985》.

Full Automatic with strong Functions

- ◆ Temperature control--DF/dielectric constant test--resistance/resistivity test--display/print, all steps are proceeded automatically.
- ◆ The set has repeat test function for the same oil specimen in the cup.
- ◆ Computer interface for test, data process, or software upgrade of the set.
- ◆ Big LCD and internal calendar clock.

Safety

- ◆ Test voltage is designed with small power components. The maximum output current is less than 10mA and will shut off within 10mS in fault state. This test power is isolated to main power.
- ◆ Heating power is isolated to main power.

Specification

Capacitance

Range:	1pF ~ 160pF
Resolution:	0.001pF
Accuracy:	±1% of the reading±0.001pF

Dielectric constant

Range:	1.0-10.0
Accuracy:	±1% of the reading

Dissipation Factor tanδ

Range:	0-4.910
Resolution:	0.0001
Accuracy:	±1% of the reading±0.0001

Resistivity

Range:	2.5MΩM~20TΩM
Accuracy:	±10% of the reading

Test Voltage

AC Test Voltage:	1000V~2000V (RMS)
Frequency:	50/60Hz (crystal time based)
DC Test Voltage:	500V

System

Computer interface:	RS232
Internal Printer:	Epson

Cup Parameters:

Controlled Cup Temperature:	10~110 degree centigrade
Electrode space between:	2mm gap (3 electrodes, 10ml volume)
Empty Cup capacitance:	60±5pF
Empty Cup DF:	< 0.005%

Environmental Conditions

Operating Temperature:	-10° C ~ 40° C
Humidity:	< 90%

Power Supply

Voltage:	220V±10%
Frequency:	50/60Hz
Power:	300W

Weight and Dimension

Dimensions:	50×250×300 (W x H x D)
Weight:	9kg

For further information please contact:

Sangor Technology

Add: 9F, Founder Tower No.1122 Xin Jin Qiao Rd.
Pudong, Shanghai, 201206, China

Tel: 86-21-58999552 58999556

Fax: 86-21-68482953 50323350

E-mail: info@samgor.com

Http:// www.samgor.com

